- ANSWEP 1 OF 1 CAPLUS COPYRIGHT 2002 ACS a Lil 1975:74500 CAPLUS AN 82:74500 DN Preservation of hides TΙ IN Bol'shakov, A. S.; Zharinov, A. I.; Fomin, A. K.; Boreskov, V. G.; Kudryashov, L. S. Moscow Technological Institute of the Meat and Dairy Industry PA U.S.S.P. SO From: Otkrytiya, Izobret., Prom. Obraztsy, Tovarnye Znaki 1974, 51(22), 83. CODEN: UPXXAF DT Patent LA Pussian IC C140 41-2 (Leather and Related Materials) CC FAN.CNT 1 APPLICATION NO. DATE KIND DATE PATENT NO. SU 432197 T 19740615 SU 1973-1909305 19730413 <--PΙ For increasing the quality of hides and for simplifying the process the AB hides were preserved by cleaning and salting in the presence of a moisture absorbing reagent, e.g. poly(vinylpyrrolidinone) (I) [9003-39-8]. The process was carried out by adding 0.5-10.0 (based on hide wt.) I after salting. hide preservation salt polyvinylpyrrolidinone IT Hide (preservation of, polyvinylpyrrolidinone in)
  - IT 9003-39-8 EL: USES (Uses)

(in hide preservation)

## XP-002137496

AN - 1975-28534W [17]

A - [001] 012 04- 101 393 431 445 477 688

CPY - MOME-R DC - A97 D18

FS - CPI

IC - C14C1/02

MC - A04-D05 A12-W D07-B

PA - (MOME-R) MOSCOW MEAT MILK IND INS

PN - SU432197 A 19741105 DW197517 000pp

PR - SU19731909306 19730413

XIC - C14C-001/02 AB - SU-432197 If hides are cleaned, salted, stored, and water removed to preserve them, the products contain 52-65% H2O, compared with a norm of 48%, and to cut water content, 0.5-10.0% polyvinylpyrrolidone on hide wt. is added, thus Improving finished hide quality, and lessening the engineering needed. In an example, hides are trated mechanically, and up to 40% salt, on hide wt. sprinkled on the scraped sides, along with 1% polyvlnylpyrrolidone powder on hide wt. After storing for 7 days/12 degrees C, the hides are sufficiently, salted, the water

IW - PRESERVE HIDE SALT WATER REMOVE POLYVINYL PYRROLIDONE IKW - PRESERVE HIDE SALT WATER REMOVE POLYVINYL PYRROLIDONE

NC - 001

OPD - 1973-04-13

ORD - 1974-11-05 PAW - (MOME-R) MOSCOW MEAT MILK IND INS

TI - Preserving hides - by salting and water removal using polyvinyl pyrrolidone